



High Speed PTZ DSP Dome Camera



IV-SDS-730

26X, High speed PTZ DSP, Day/Night

SPECIFICATION	IV-SDS-730
Imaging Sensor	1/4" SONY Exview HAD CCD
Optical zoom	F1.6 ~ F3.8
Focal length	f=3.5 mm (wide) to 91.0 mm (tele)
View Angle	54.2°(wide end) to 2.2°(tele end)
Effective pixels(HxV)	380K pixels approx.
Scanning system	2:1 Interlace V: 59.94Hz, H: 15.734KHz
Sync system	Internal / line-lock
video output	1Vpp composite output, 75 ohm
Horizontal resolution	480 TV lines
S/N ratio	More than 50 dB
Zoom Limit	UP TO 312X (optical 26X, digital 12X)
Focusing system	Auto(normal sensitivity / low sensitivity)
Focus	Auto (sensitivity: normal, low), One-push AF, Manual, Infinity, Interval AF, Zoom Trigger AF
Minimum illumination	Normal/Night: 1/ 0.15 lux (F1.6, 1/60(1/50)sec. ICR OFF/ON) Slow shutter: 0.07/0.01 lux (ICR OFF/ON)
Gain control	Auto
White balance	Auto, ATW, One-push
Electric shutter	1/1 to 1/10,000sec. 22 Steps
Auto slow shutter	On/Off (Max 1.0S)
AE control	Auto, Manual, Priority mode, Bright, EV compensation, Back-light compensation
EV compensation	-10.5~+10.5dB(15 steps)
BLC / Auto Flip	On / Off
Alarm / Flickless	Yes
Day/Night mode	Auto / manual
Mirror Image	Yes
Pan range / Tilt range	360° continuous / 92°
Manual Pan Speed	0.1 - 90°/s / 0.1o/s: max dig. zoom ; 0.4o/s :max opt. zoom
Manual Pan Speed (Turbo)	150°/sec
Manual Tilt Speed	0.1 - 45°/s / 0.1°/s: max dig. zoom ; 0.4°/s :max opt. Zoom
Present Speed	Pan: 430°/sec(max); Tilt: 200°/sec (max)
Proportional P/T	Yes
Pan/Tilt Limit	user definable
Zoom limit	x26,x52,x104,x208,x312
Programmable Present	256 points
Programmable Tours	4 pattern tours memorizing up to 6 mins of manual control
Privacy Zone	On / off, up to 24 zones (3D Privacy Zone)
ScanFunction	Random, frame and auto-scan selectable
Alarm	6 inputs / 1 output
Present titles	Max 20 characters
Password protection	alphanumeric Dome OSD setup protection
Other superior Function	Super Fine Pan for 0.02° Accuracy / Motion Detection / Scheduling
Remote control	MESSOA P/D (Also support Pelco-P/D, GE, Bosch, Ernitec)
Specail Commands	support absolute(X, Y, Z) position
Interface	RS485 (2-wire)
Baud Rate	2400,4800,9600,19200 bit/s(DIP-sw selectable)
Operating temperature	-40 °C ~ 60° C
Operating humidity	20% ~ 80% RH
Storage temperature	-20°C ~ 60° C
Dimensions(O x H)	216.6mm X 324.0mm (H)
Weight	3500g approx
Power requirement	AC24V
Power consumption	46W (max.)
Vandal proof	750KG (1653 lb) impact resistance
Water proof	IP67 (With Heater and Blower)