



# Weatherproof IR Bullet Camera

## IV-BVDN760

### Features:

- . 1/3" SONY Super HAD CCD
- . High Resolution (530 TV Lines)
- . DC Iris Vari-focal Lens(3.8~9.5mm)
- . Built-in IR LED 18EA and Sensor 1EA
- . IR Visible Range : MAX 20m
- . Day&Night (ICR)
- . Min. Illumination : 0.00 Lux (IR LED On)
- . Weather Proof Housing
- . 12VDC
- . IP 65



| SPECIFICATION            | IV-BVDN760                                       |
|--------------------------|--|
| Signal System            | NTSC   |
| Scanning System          | 2:1 Interlace                                    |
| Scanning Frequency(H)    | 15.734kHz  |
| Scanning Frequency(V)    | 59.94Hz  |
| Image Sensor             | 1/3" SONY Super HAD CCD                          |
| Total Pixels Number      | 811(H) x 508(V) 410K                             |
| Effective Pixels Number  | 768(H) x 494(V) 380K                             |
| Horizontal Resolution    | 530 TV lines                                     |
| Video Output Level       | 1.0 Vp-p (75Ω, composite)                        |
| S/N Ratio                | More than 48dB (AGC off)                         |
| Lens                     | DC Iris Vari-focal Lens(3.8~9.5mm)               |
| Angle of View            | f=6mm: 60°                                       |
| Min. Illumination        | 0.00 Lux (IR LED on)                             |
| White Balance            | Auto   |
| AGC                      | On/Off   |
| BLC                      | On/Off   |
| Flickerless              | On/Off   |
| Electronic Shutter Speed | 1/60~100,000sec                                  |
| IR LED & Sensor          | 850nm IR LED 18EA, Sensor 1EA                    |
| IR LED Lighting Distance | Max. 20m   |
| Input/Output Connector   | Power input(red jack), Video output(yellow jack) |
| Supplied Voltage         | 12VDC  |
| Dimensions               | 3.07"(Ø) x 6" (H) / 78.0(Ø) x 150.0(H) mm        |
| Weight (Net)             | Approx.28.2 oz / 800g                            |