



COLOR DSP Varifocal Bullet Camera

IV-TCD-23Y4

Features:

- . High performance 1/3" color camera with excellent sensitivities
- . Water resistance test (IP66) with bracket for indoor or outdoor use
- . Outdoor housing with camera, lens, bracket and housing as a set
- . Auto gain control (AGC)
- . Auto white balance (2000°K ~ 10000°K)
- . Integrated Auto Iris Vari-focal lenses provide wide range lens middle distance:2.8~10mm ultra distance:5~50mm
- . Easy to install



SPECIFICATION	IV-TCD-23Y4
Image Sensor Device	1/3. Color HI RES CCD interline
Pixel Number	NTSC 771 (H) X 492 (V) PAL 737 (H) X 575 (V)
Scanning system	NTSC standard 525 lines, 30 frames/sec PAL standard 625 lines, 25 frames/sec
Horizontal resolution	More than 480 TV lines
Synchronizing System	Internal
Gamma Correction	0.45
Minimum Illumination	0.8 LUX / F1.4
Mechanical iris	Auto iris lens (DC drive)
White Balance	Auto (2000°K~10000°K)
BLC	Yes
Video Output Level	1.0 VP-P / 75 Ohm
Video S/N Ratio	48db(AGC OFF)
Operating Temperature	-10°C~50°C
Storage Temperature	-20°C~80°C
Power Requirement	DC12V ±10%
Power consumption	130 mA (MAX) For DC12V
Dimensions (L x W x H)	200 x 89 x 155 mm / 8" x 3.5" x 6.1"
Weight	790g / 27.9 oz
Vari-focal lens type	2.8 ~ 10.0 mm / 5.0 ~ 50.0 mm auto iris DC drive