



Weatherproof, Vandalproof Vari-focal Bullet Camera

IV-BVH3426

Features:

- . IR projecting distance 150 feet in dark view
- . Easy to install for both indoor and outdoor application.
- . Integrated auto iris vari-focal IR lens which provide wide zooming range with adjustable focal length in 2.9 ~ 10mm
- . Anti-Thunder circuit prevents tube struck by thunder
- . Weatherproof, Vandalproof, IP-66
- . Option: true day & night solution (with mechanical switching IR-Cut filter)



SPECIFICATION	IV-BVH3426
Image device	1/3" color CCD sensor interline
Effective picture elements	NTSC 768(H) x 494(V)
Scanning system	2:1 interlace
Synchronizing system	Internal
Horizontal resolution	More than 480 TV lines
Electronic shutter control	off
Gamma	0.45
Minimum illumination	1.2 Lux/F1.8 IR on : 0 Lux
Video output level	1Vp-p / 75Ω
Video S/N ratio	48 dB (AGC off)
White balance	Auto (2500°K~9500°K)
Backlight compensation	Yes
Storage temperature	-30°C~80°C
Operating temperature	-10°C~50°C
Power requirements	DC 12V, AC 90~260V
Power consumption (DC12V)	570mA
AGC function	Yes
Emitting wavelength of LED	850nm
Emitting angle of LED	40° / 20°
illumination distance	150 feet
Dimensions	9" (L) X 4.25" (W) X 3.75" (H) / 230 (L) X 108 (W) X 95 (H) mm
Weight	3.5 lbs / 1400g
Wari-focal IR lens	2.9~10 mm with auto IRIS