



Outdoor IR Bullet Camera

IV-TC32LI

Features:

- . 24-hour operational camera with perfect picture performance
- . IR camera built-in 24 / 35 IR LEDs for 15~20/35~40m range in dark view
- . Unique looks for outdoor / indoor application
- . Packing camera, lens, bracket as a set
- . Water resistant of aluminum die-cast pass IP 66 test
- . Easy to install



SPECIFICATION	IV-TC32LI
Image device	1/3" color CCD sensor interline
Scanning system	NTSC 510(H) x 492(V)
Synchronizing system	2:1 interlace
Horizontal resolution	Internal
Electronic shutter control	More than 380 TV lines
Gamma	Auto-Electronic Shutter (1/60~1/100000 sec) NTSC
Minimum illumination	0.45
Video output level	1.0 Lux/F1.8 IR on: 0 Lux
Video S/N ratio	1Vp-p / 75Ω
White balance	48 dB (AGC off)
Backlight compensation	Auto (2500°K~9500°K)
Storage temperature	Yes
Operating temperature	-30°C~80°C
Power requirements	-10°C~50°C
Number of IR LED	DC 12V±10%
Power consumption (DC12V)	24 PCS
Projecting range of IR LED lighter	170mA
Dimensions	About 15~20m
Weight	166 (L) X 88 (W) X 140 (H) mm
Lens standard	590g