



Weather Proof IR Cameras

IV-BM-5562NIR

Features:

- . 1/3" SONY Super HAD CCD
- . 480TVL High Resolution
- . Day & Night (ICR)
- . Digital Slow Shutter
- . 30x Optical Zoom/10x Digital Zoom
- . AWB, AGC, BLC, Flickerless
- . Built-in IR LED & Sensor
- . Extra Video-out port for Easier Installation
- . Built-in Fan & Heater
- . Cable Through Type Camera Bracket



SPECIFICATION	IV-BM-5562NIR
Signal System	NTSC
Scanning System	2:1 Interlace
Scanning Frequency (H)	15.734kHz
Scanning Frequency (V)	59.94Hz
Image Sensor	1/4 inch SONY Super HAD CCD
Total Pixels Number	811(H) x 508 (V) 410K
Effective Pixels Number	768 (H) x 494 (V) 380K
Horizontal Resolution	480 TV Liens
Video Output Level	1.0Vp-p (75Ω, composite)
S/N Ratio	More than 48dB (AGC off)
Digital Zoom Ratio	10x (On/Off)
Lens	30x Optical Zoom (F 1.6(W), F3.7(T) f=3.9 ~ 85.8mm) Video AF
Min. Illumination	1Lux (Color), 0.5Lux (B/W), 0.001Lux (DSS 128FLD), 0.000Lux (IR LED ON)
Day&Night Type	Electronic Sensitivity-up (DSS), ICR (Sensor Type)
Electronic Shutter Speed	1/60~1/10,000sec
Supplied Voltage	12VDC (9.6~13.2VDC)
Power Consumption	Max. 3W at DC12V
Dimensions	272.1(W) x 220.2(H) x 356.5(D)mm