



## IR Bullet Camera

### IV-DH628DN

#### Features:

- . Sony 1/3" Super HAD High Sensitivity Color CCD
- . Ultra Low Light 0 Lux
- . High Resolution 580 TVL Color
- . Privacy Masking for up to 8 areas
- . Built-In IR Illuminator
- . Digital Image Stabilizer reduces vibration
- . Electronic Shutter up to 1/120,000
- . Built-In Motion Detection (8 Zone)
- . AC 24V / DC 12V / Dual Voltage



SPECIFICATION	IV-DH628DN
Pick Up Device	Sony 1/3" Super HAD Color CCD
Lens	2.9 ~ 10mm
Picture Elements (Pixel)	NTSC: 768H x 494V
Horizontal Resolution	580 TVL Color; 700 TVL Black & White
Sync. Frequency	NTSC:15.734 KHz /60 Hz PAL:15.625 KHz / 50 Hz
Clock Frequency	NTSC:28.636 MHz PAL:28.5 MHz
Scanning System	2:1 Interlace
IR Illuminator	18
IR Range	80 ft
Sensitivity D/N	0 Lux
Brightness (Sens-up)	Auto / Off (Adjust x2 ~ x 256)
Synchronization	AC: Line Lock / DC: Internal
Day/Night	Color / B/W / HLC
Auto Gain Control	Low / High / Off
Back Light Compensation	Off / BLC / HLC
Digital Noise Reduction	On / Off (1~32 Levels)
Electronic Shutter	1/60 ~ 1/120,000 sec
White Balance	ATW / AWC / Manual / Outdoor / Indoor
Digital Image Stabilizer	On / Off
Privacy	On / Off (8 Zone)
S/N Ratio	52 dB (AGC Off, Weight On)
Aperture Correction	2H mode enhancement
Power Consumption	300mA 24V DC; 450mA 12V DC
Video Output	1 Vp-p, 75 Ohms Composite
Power Supply	AC: 24VAC, DC: 12VDC dual voltage
Dimension (mm)	TBA
Weight	TBA
Weather Proof	IP 67
Storage Temperature	-4 °F ~ 140 °F / -20°C~+60°C
Operating Temperature	14 °F ~ 122 °F / -10°C~+50°C