



## Vandal Proof Dome Camera

### IV-DV502F

#### Features:

1/3" SONY Super HAD CCD  
 Day/Night Function  
 600 TVL  
 0.3 Lux @ F1.2 (50 Color)  
 0.002 Lux(Sens-Upx128)  
 Digital Noise Reduction  
 On Screen Display Menu  
 Privacy Zone  
 Motion Detection  
 3-Axis  
 IP68



SPECIFICATION	IV-DV502F
Resolution	600 TVL
Sensor	1/3" SONY Super HAD CCD
Total Pixels	NTSC: 811x508 410k Pixels; PAL: 795x595 470k Pixels
Effective Pixels	NTSC 768x494 380k Pixels; PAL: 752x582 440k Pixels
Scanning System	2:1 Interface
Synchronization	Internal/Line Lock
Frequency	NTSC:Horizontal15.734kHz/ Vertical: 59.94Hz; PAL:Horizonta 15.625kHz/Vertical 50Hz
S/N	More than 50dB
Video Output	CVBS 1.0Vp-p/75ohm
Min. Illumination	0.3 Lux @ F1.2 (50 IRE, AGC High, DNR Hight, 0.002 Lux (Sens-Up x128)
White Balance	ATW/AWC/Manual/Outdoor (1800k ~ 10500k)
ES Speed	Auto/Manual (NTSC:1/60sec~1/120000sec;PAL:1/50sec~1/120000sec)Selectable/Flickerless
Lens	2.8-12mm
O.S.D	Built-In
Backlight Compensation	Low, Mid, High, Off Selectable
Gain Control	Low, Mid, High, Off Selectable
SDNR	Low, Mid, High, Off Selectable
Day/Night	Auto/On
Motion Detection	On/Off 4 Zones
PRIVACY	On/Off 4 Zones
MIRROR	On/Off
Operating Temp.	-10C ~ 50C / 30%~80% RH
Storage Temp.	-20C~60C / 20%~90% RH
Power	DC 12V/ AC 24V Dual Power
Protection Rating	IP 68