



3-Axis Vandal Resistant Mini Camera

IV-TCDF-34V3 (HI-RES)

Features:

- . Quick installation for mounting on ceiling or wall.
- . Image position adjustable by manual 3-Axis.
- . Ultra compact mini dome 3.7"(Ø) x 2.7"
- . Suitable for applications like elevators, buses, etc...
- . Various lens options, 4mm standard.
- . Easy to install, simple to operate.



SPECIFICATION	IV-TCDF-34V3 (HI-RES)
Image device	1/3" color CCD interline sensor
Effective picture elements	NTSC 768(H) x 494(V)
Scanning system	2:1 interlace
Synchronizing system	Internal
Horizontal resolution	More than 480 TV lines
Electronic shutter control	Auto-Electronic Shutter:(1/60~1/100000 sec)NTSC
Gamma	0.45
Minimum illumination	1.2 Lux/F1.8
Video output level	1Vp-p / 75W
Video S/N ratio	48 dB (AGC off)
White balance	Auto (2500°K~9500°K)
Operating temperature	12°F~122°F
Power requirement	DC 12V±10%
Power consumption(DC12V)	110mA
Dimensions	3.7" (Ø) x 2.7" (H)
Weight	12.3 oz
Fixed Lens	STD: 4.0mm; Optional: 6.0 / 8.0 12.0mm