



Vandal-Resistant Dome Camera

IV-V2867NVF

Features:

- 1/3" SONY Super HAD CCD
- Built-in DC Iris Vari-focal Lens(2.8-10.5mm)
- High Resolution 550TVL
- Min. Illumination:
- Day (0.3 lux) Night(0.00Lux, IR LED On)
- SDNR
- 3-Axis Mechanism for Free Lens Rotation
- Vandal Proof Dome Housing
- Day & Night Function
- OSD, Privacy Zone, Mirror Function
- Eclipse Function
- 12VDC/24VAC Dual Voltage



SPECIFICATION	IV-V2867NVF
Signal System	NTSC
Scanning System	525 Lines 2:1 Interlace
Scanning Frequency(H)	15.734 KHz
Scanning Frequency(V)	59.94 Hz
Image Sensor	1/3" SONY Super HAD CCD
Sync. System	Internal
Total/Effective Pixels Number	410K/380K
Horizontal Resolution	550 TVL
S/N Ratio	More than 48dB (AGC Off)
Lens	DC Iris Vari-focal Lens (2.8-10.5mm)
Min. Illumination	0.3 Lux(Day), 0.00 Lux(Night)
Special Function	OSD, Privacy Zone, Mirror
Electronic Shutter Speed	Auto (1/60~1/100,000sec)
Day & Night	DSS & Auto ICR
Supplied Voltage	AC 24V/ DC 12V (9V~15V)
AGC, BLC, Flickerless	On/Off
Dimensions	100" (Ø) x101.14" (D) mm
Supplied Voltage	12VDC/24VAC

IDView Technologies • 12000 Ford Rd. Suite 110 • Dallas, TX 75234 • www.digitalidview.com