



Outdoor Pixim WDR Dome Camera

IV-VRCD-6371

Features:

- . Pixim 1/3" High Sensitivity Digital Sensor
- . 690 TVL Resolution
- . Digital Day & Night
- . WDR (Wide Dynamic Range)
- . Sens-Up (2X~32X)
- . Motion Detection (4 Zones)
- . Private Masking (12 Zones)
- . Digital Zoom (8X)
- . Aluminum & Poly-Carbonated Material Housing (IP66)
- . Vandal Resistant
- . Built-in 3-Axis Bracket



SPECIFICATION	IV-VRCD-6371
Image Sensor	PIXIM 1/3" High Sensitivity Sensor
Effective Pixels	758(H) x 540(V)
Synchronization	Internal / Line Lock
Scanning System	2:1 Interface
Frequency	NTSC: 15,734KHz(H)/59.94KHz(V), PAL: 15,625KHz(H)/50.00KHz(V)
Horizontal Resolution	690TVL
Min. Illumination	0.1 Lux
S / N (Ratio)	More than 50dB
Video Output	CVBS: 1.0 Vp-p, 75 ohm Composite
On Screen Display	Built-in
Camera Title	Available
Day & Night	AUTO/COLOR/BW
Backlight Compensation	ON/OFF
WDR	120dB Max. 101dB Typical
Motion Detection	ON/OFF
Privacy Masking	12 Zones
DNR	AUTO/OFF
Sens – up (Slow Shutter)	Auto/Off(Selectable x2~x32)
AGC	Low/Auto/High/Off
White Balance	ATW/ATWDes/AWC/MANUAL
Color Temperature	2,000~11,000 K
Electronic Shutter Speed	~ 1/30,720sec@F1.2
Communication	RS-485 available
Protocol	PELCO-D
Flip	Selectable
Mirror	Selectable
Digital Zoom	~ x8
Lens	2.8-10mm/F1.2
Input Voltage	DC12V/AC24V
Power Consumption	DC12V/AC24V(Max 250mA/170mA)
Weatherproof	IP66
Operating Temperature / Humidity	-10 °C ~ +50 °C / 30~90%
Dimension (WxHxD)	(R)143.64 x 119 (mm)
Weight	Approx. 1,100g