



Super WDR Dome Camera

IV-760CV

Features:

- Pixim 1/3" DPS ORCA Chip Sensor
- High Resolution (up to 540HTVL Equivalent)
- Best WDR (Wide Dynamic Range) Function
- Digital Day & Night, 6 Privacy Zone
- Built-in OSD (On Screen Display) Menu
- Vari-Focal Auto iris zoom lens (4.0~9.0 mm)
- Place Setup for easier setting (Indoor, Outdoor, Normal, Customs, Fluorescent)
- Selectable Languages (English, German, French)



SPECIFICATION	IV-760CV
Image Sensor	1/3" DPS ORCA
Effective Pixels	720(h) x 540 (v)
Horizontal Resolution	Max 540 TVL
Scanning Frequency	15.734KHz(H), 59.944(V)
Video Io Select	NTSC / PAL
Min. Illumination	Color : 0.4 Lux (F:1.2), (Sense-up 32x : 0.08Lux)
Day & Night	D&N Function by Digital Change : Auto/Off /On
White Balance	Auto / ATW DESAT / AWC / Manual
DSS	Off / 2 fields ~ 32 fields / Custom
DNR	On / Off
Lens	4.0mm~9.0mm DC auto iris lens
Flip	Off / H.FLIP/ V.FLIP/ H-H.FLIP
AGC	Low / Middle / High
Camera ID	On / Off
Wide Dynamic Range	Max 120dB /17 -bit
Privacy Zones	Off / On (White, Black, Red)
S/N Ratio	More than 50dB
Video Output	Composite video output 75 ohm terminated
OSD	Built-in
Sync. System	Internal
Operating Humidity	30 % ~ 90 % RH
Operating Temp.	14 °F to 122 °F (- 10°C to 50°C)
Dimension	145(D)X103(H)mm
Weight	About 40 oz (1.2Kg)
Material	Plastic body, Bubble(120mm)
Power Consumption	250mA
Power Supply	DC 12 V(10.2V~14.5 V)