





Water Resistant Color Dome Camera

IV-TCDV-0362

Features:

- . Water resistant
- . Easy installation and remove
- . Optional outdoor bracket
- . With vari-focal lens 4~9mm (auto iris)
- . Vandal resistant withstand 10 pounds sledgehammer



SPECIFICATION	IV-TCDV-0362
Image device	1/3" CCD SENSOR interline
Effective Picture elements	NTSC 510(H)x492(V)
Scanning system	2:1 interlace
Synchronizing system	Internal
Horizontal resolution	380TV Lines
Video output level	1Vp-p / 75 ohm, composite
Gamma	0.45
Mechanical IRIS	Auto Iris Lens
Minimum illumination	1 LUX/F1.8
Video S/N ratio	46dB (AGC OFF)
White balance	Auto white balance (2000°K~10000°K)
Operating temperature	14 °F ~ 122 °F / -10°C~50°C
Storage temperature	-22 °F ~ 176 °F (-30°C~80°C)
Power requirements	DC12V ± 1.2V
Power consumption	DC12V Typical 180mA
Dimensions	4.25" (Ø) x 3" (H) / 108 (Ø) x 75 (H) mm
Weight	1.4 lbs / '640 g
Vari-focal lens Type	Standard: 4-9mm auto iris lens Optional: 2.8~6mm auto iris lens