



Vandal Resistant Dome + IR Camera

IV-TCD-23H2/H4

Features:

- . Low light solution.
- . Water resistant pass IP66.
- . Easy remove and installation.
- . Built in 12 IR LEDS with projecting distance 10~15m.
- . Vandal resistant withstand 10 pounds sledge hammer.
- . Outdoor bracket as option (blower included)



Bracket Option : KO-B320



SPECIFICATION	IV-TCD-23H2(MID-RES)	IV-TCD-23H4(HI-RES)
Image device	1/3" color CCD sensor Interline	
Effective Picture elements	NTSC 510(H) x 492(V)	NTSC 768(H) x 494(V)
Scanning system	2:1 Interlace	
Synchronizing system	Internal	
Horizontal resolution	More than 380 TV lines	More than 480 TV lines
Electronic shutter control	Auto-Electronic shutter (1/60~1/100000 sec) NTSC	
Gamma	0.45	
Minimum illumination	1.0 Lux/F1.8, IR on: 0 Lux	1.2 Lux/F1.8, IR: 0 Lux on
Video output level	1Vp-p / 75 Ohms, composite	
Video S/N ratio	48dB (AGC off)	
White balance	Auto	
Backlight compensation	Yes	
Operating temperature	-30°C ~ 80°C	
Storage temperature	-10°C ~ 50°C	
Power requirements	DC12V ± 10%	
Power consumption	DC12V/180mA	DC12V/210mA
	About 10~15m	
Dimensions	108 (Ø) x 75 (H) mm	
Weight	530 g	
Lens Standard	6.0mm / F2.0	