



IP Camera

IV-101LC-RT

Features:

- . 1/3 inch interlaced CCD
- . Motion detection
- . IEEE 802.11b standard wireless access
- . C or CS-lens mount
- . Multi-level and multi-user secure management
- . Simultaneously export analogs and digital images
- . Built-in Web Server and network interface



SPECIFICATION	IV-101LC-RT
SD Socket	SD storage Card (option)
CCD sensor	1/3 inch interlaced CCD
CCD resolution	NTSC: 270 Kpixels; PAL: 320 pixels
Video Output	1.0 Vpp, 75 ohm, composite, negative
Network throughput	1.5 MB/sec
Horizontal resolution	340 TV lines
Exposure	BLC / AGC / AWB
Electronic shutter	NTSC: 1/60 - 1/100,000 sec
Sensitivity	0.8 Lux @ F1.2
Auto iris type	DC-iris (support)
Compression	MJPEG
Picture size	4 ~ 64 KB
Video fine tune	Brightness, BLC, Saturation, Hue, Sharpness
Water marker	Digital Signature
Communication port	RS-232
Network Interface	802.11b Standard for 2.4 GHz wireless
Network Protocol	TCP/IP, UDP, DHCP, HTTP, SMTP, SNMP, FTP, ICMP, DDNS, DNS
Wireless Bit Rate	11, 5.5, 2, 1 Mbps
Wireless Security	WEB Encryption 64-bits and 128-bits
Wireless Output Power	10 dBm (MAX)
Motion detection	Advanced MD (zone, position, sense)
Alarm I/O	Yes
Secure password /Username	Multi-layer / Multi-user
SD Socket	Yes
Firmware Upgrade	Upgrade via SD card or RS-232
Power input	5 V DC / 2A
Operating environment	Requires proper environmental housing for outdoor use
Operating temperature	5 - 50 °C (41 - 122 °F)
Regulation	FCC, CE
Dimensions (H x W x D)	62 x 50 x 95 mm / 2.4" x 2" x 3.5"
Weight	11.2 oz
Function of Client PC	
Operating System	Windows Linux
Browser	IE 5.x, 6.x Netscape
Camera setup	Camera setup Username / IP / PROXY / Password / Time / Date / Motion / Alarm
Multi-camera link	4 camera
Viewer	1 / 4 SPLIT
Save file format	JPEG / AVI