



CCTV Remote Control Keyboard

IV-7313-S

Features:

- . RS-485 port for CCTV system control
- . Built-in DSCP, Pelco D&P protocol
- . Joystick control of PTZ functions
- . Preset position and Cruise control
- . User-friendly interface
- . Firmware upgrade via RS-232
- . Control Dome cameras, P/T/Z Receivers, Multiplexers, DVR's
- . 16 Cameras, 1 Multiplexer
- . Optional 3-axis joystick



SPECIFICATION	IV-7313-S
Power	12 Volt DC
Power Consumption	5W
RS-485 port	RJ-11, Terminal Blockx1
RS-232 port	D-SUB 9pin x 1
Device on Bus	16 Cameras 1 Multiplexer
Pan/Tilt Control	Manual Pan/Tilt
Preset:	128 maximum
Auto Pan:	On/Off
Sequence:	4 Minimum
Cruise:	On/Off
Lens Control	N/A
Zoom:	Tele/Wide
Focus:	Near/Far, Auto
Iris:	Open/Close, Auto
Camera Setup	Yes
Multiplexer Control	Channel select: 16
Multiplexer Setup	Yes
Dimension (L x W x H)	330 x 175 x 65 mm (139 x 6.9 x 2.6 inches)
Operation Temperature	0°~40° (32° to 104°)
Operation Humidity	Below 90%, non-condensing
Weight	1.5kg (3.3 lbs)