



Speed PTZ Dome Control Panel

IV-SAC760

Features:

- RS-485, RS-422 and RS232 multi-protocols
- Controls up to 256 speed domes directly
- Compatible with SDS620/SDS640/SDS660/SDS680
- Presets, tour, auto scan, random scan and frame scan control
- RS232 port for computer to control cameras via this control panel
- Support Pelco-P/Pelco-D protocol



SPECIFICATION	IV-SAC760
Connector	
Remote control	RJ45, 8-pin, modular female)
Connect to PC	RS232, D-sub 9-pin(female)
Communication	
Interface	RS-485 / RS-422 / RS-232
Protocol	Pelco-P, Pelco-D
Baud	1200, 2400, 4800, 9600
Communication parameters	8 data bits, no parity, 1 stop bit
General	
Keypad	Mechanical
Joystick	2-axis, vector-solving, auto return to center
Led display	Green LED, 7-segment display, 3 cells
Shift indicator	Red LED
Dimensions(WxHxD)	175mm x 248mm x 55mm
Power requirement	DC12V / AC24V
Power consumption	2.5W
Weight	1.2kg approx.
Environment	
Operating temperature	-10 °C to 50 °C
Operating humidity	10%~90% RH, no-condensing
Storage temperature	-20 °C to 60 °C