





Vandal Resistant Dome Housing

IV-DOME-59-I (Indoor)

IV-DOME-59-O (Outdoor)



1/2" Conduit Knockout



8.49
215.8

1" NPT Pipe Entrance



Features

Rugged polycarbonate camera enclosure

Simple camera installation

Designed for use with IP and analog camera systems

Accepts camera and lens up to 4" in length

Weatherproof IP 66

Surface mount or Pendant mount, using a 1" standard pipe thread

Includes a pendant mount option for a 1" aluminum gooseneck wall mount

Outdoor models available with thermostatically controlled heater/blower

Specification

Size	8.5"x8.5"x8.4"
Weight	2.3 Lbs
Construction	Polycarbonate
Power Requirements	Camera: AC 24V; Heater and Blower: 40 watts max
Operating Temperature	-40° F to 122° F (Outdoor Models)
Heater Activates at	60° F
Operating Humidity	Up to 100%

Outdoor Model IV-DOME-59-O for 5.9" Fixed Camera

Vandal resistant polycarbonate surface mount dome.

Clear dome w/ AC 24V input, heater/blower, 1 fixed camera bracket.

Indoor Model IV-DOME-59-I for 5.9" Fixed Camera

Vandal resistant polycarbonate surface mount dome.

Clear dome, 1 fixed camera bracket.