



Speed Dome PTZ Camera

IV-10XPTZ Kit

Features:

- . Built-in 1/4" Sony CCD Sensor
- . Built-in 10X Optical and 10X Digital Lens
- . Built-in OSD Function
- . Built-in Removable ICR Filter
- . Multi Protocol Communication, Pelco D, and P



PTZ Controller

SPECIFICATION	IV-10XPTZ Kit
SYNC System	Internal Mode/ External (AC Lock) Mode ($\pm 1\text{Hz}$)
Scanning System	1:2 Interlace
Image Pickup Device CCD Sensor	ICX228AK (NTSC)
Effective Pixels	768 (H) X 494 (V) (NTSC)
S/N	More than 46 dB ($\gamma = 1$, AGC OFF, APC OFF, Y-out)
Horizontal Resolution	480 TV Lines
Lens	F1.6(W) ~ 1.9(T) f=3.7(W) ~ 37.8(T)mm
Zoom	10X Optical Zoom and 10X Digital Zoom
White Balance	ATW/AWB/FIX (Zero Color Rolling)
ALC	Auto/Fix (OSD Control)
AGC	+24dB (Max)
BLC Function	48 Zone BLC (OSD Control)
ICR Function	YES
Minimum Illumination	1.5 Lux(F1.8/50IRE) ICR ON 0.02 Lux
Electronic Shutter	AES: 1/60(1/50) ~ 1/120,000 sec. Manual: 8 Step
GAMMA Correction	0.45 / 1
Video Signal Output	1.0Vp-p / 75 Ω
External Control	RS485
Pan	Speed 0.5 ~ 30°/s
Tilt	Speed 0.5 ~ 30°/s
Preset	32 Preset Positions (Max)
Auto Cruise	6 Auto Cruising Tracks (Max)
Operation Temperature	-10°C ~ 50°C
Operation Humidity	Within 85% RH
Power Source	DC12V \pm 0.5V, 6W (Max)