



12 channels Video Server

IV-CAMoIP-12CH

Features:

- . Selectable MPEG-4/MJPEG compression
- . CIF up to D1 resolution at 30 FPS (per channel)
- . Multi-stream with variable frame rate in the same compression
- . Built in Switch / Router
- . Hardware motion selection
- . Dual Uplink
- . Designed to be rack mounted



SPECIFICATION		IV-CAMoIP-12CH
Video	Resolution	QCIF/CIF/VGA/D1
	Compression	MPEG4/MJPEG (dual streaming for any 2)
	Frame rate	Up to 30fps @NTSC (adjustable)
	Bit rate control	Supports Variable bit rate (VBR), 64Kbs ~ 2Mbs
	Other features	Dynamic information on screen Motion detection
Network	Interface	Ethernet wired, 10/100/1000T, Auto MDI/MDI-X
	Transfer rate	148,800pps for fast Ethernet port
	Standard	IEEE 802.3/802.3u/802.3ab/802.3x/802.3ad/802.1d/802.1p/802.1Q/802.1x/802.1ab RFC 3418/2011/1493/2674/1215/1643/1757
	Benefits	4Mbs packet buffer
	QoS	IEEE802.1p class of service
	DHCP	Provide DHCP Client/Server
	DNS	Provide DNS client feature and primary / secondary DNS server
Connectors and Peripherals	Protocols	TCP/IP, UDP, HTTP, DHCP, DNS, DDNS, NTP, RTP/RTSP, SMTP, FTP, UPnP
	Video-in	12x CVBS, BNC, male / 1.0Vp-p, 75 ohms
	Network	2x RJ-45 wired, 10/100/1000T base-tx
	Reset Button	Factory default
Physical Characteristics	LEDs	System status (per channel)
	Power Supply	AC 100~230V, 50~60Hz, 0.8A(maximum)
	Power Consumption	60Watt
	Working Temperature	0 ~ 45° C
	Storing Temperature	-20 ~ 70° C
	Dimensions	17.3" (W) x 3.14" (D) x 1.73" (H)
	Installation	19" rack mount
Safety	CE / FCC / RoHS	
Software	Web browser	Microsoft Internet Explorer 7.0 and above
	PTZ	Pelco-D/P
	Security	Password protection: configured by administrator, 2 levels, administrator / user
	Utility	eSearch for scanning video server 12 channels NVR software