



Enterprise 16 CH MPEG4 DVR

NW-STA-5016

- . 5th Gen DVR offering advance features in digital recording
- . 4 CH audio
- . Supports call, spot monitor
- . 4 X and 16 X Digital Zoom
- . CMS software linking 64 cameras



SPECIFICATION		NW-STA-5016
VIDEO		
Input Channel		16 CH
Loop Through Output		16 CH
Video Standard		Auto / Jumper / NTSC / PAL
Live Frame Rate		480 FPS
AUDIO		
Audio In / Out		4 CH / 1 CH
RECORDING		
Compression		MPEG4
Resolution	NTSC	720(H)x480(V), 720(H)x240(V), 360(H)x240(V)
Speed	360 x240	Max 120FPS
	720 x240	Max 60FPS
	720 x480	Max 30FPS
HDD Storage	Internal External	2HDD + CD R/W (DVD R/W), S-ATA compatible type USB 2.0
REMOTE SURVEILLANCE		
Monitoring Environment		CMS, Client and IE Browser
Real Time		App. 16 CH Full Motion Transmission
ALARM		
Sensor Input		16 Ports
Alarm Output		4 TTL-Out (Programmable), Terminal
CONNECTOR		
Main Monitor Output		VGA / BNC / S-Video
S-Video (Main TV)		BNC S-Video 1 Port (4 Pins mini DIN)
Spot Monitor Output		BNC 1 Port
VGA Output		1 Port (15 Pins female DSUB)
Audio Input (Mono)		RCA 4 Audio Jack (Live Only)
Audio Output (Mono)		RCA 1 Port
HDD Extension		USB 2.0
Firmware Upgrade		Remote firmware upgrade by CMS
Ethernet		RJ-45, 10 / 100 Mbps
USB 2.0		Front 2 Ports, Back 1 Port
ELECTRICAL		
Power Source		115/230 VAC (50~60 Hz)
Power Consumption		App. 50 ~ 60 Watt
BACKUP		
Digital Backup		CD-R,CD-RW, DVD-R, DVD-RW