



LCD Flat Panel CCTV Monitor

LM-1701
LM-1901



Specification	LM-1701	LM-1901
Display area	17-inch measured diagonally	19-inch measured
Panel size	(W) 337.92 x (H) 270.336 mm	(W) 376.32 x (H) 301.056 mm
Resolution	1280x1024(SXGA); 1024x 768(XGA)	
Screen Size	17"	19"
Dot	0.264mm (H) x 0.264mm (V)	0.294mm (H) x 0.294mm (V)
Color Resolution	16.7 M (8 bits) / 262K (6 bits) Optional	
Brightness	300 cd/m ² / others optional	
Contract Ratio	500 : 1 / others optional	
Viewing Angle	Horizontal: +/- 80° & Vertical: +/- 80°	
Response Time	8ms	
Power Button	On / Off	
OSD control button	Menu / Select / ◀ / ▶ / Auto	
Color adjustment	Contrast, Brightness, Color Temperature, Color Adjust, Hue Saturation	
Picture adjustment	H-Position, V-Position, Clock, Zoom	
Function adjustment	Auto Adjust, Auto Position, Auto Phase, Auto Clock, Auto Color	
OSD Menu	Language, OSD H-Position, OSD V-Position, OSD Timer, Translucent	
Miscellaneous	Signal Source, Reset, Power Saving, Version	
Video Input signal	VGA 0.7Vp-p @75 ohms / (BNC/RCA) / 1Vp-p @75 ohms	
Video Output signal	Composite (BNC) 1Vp-p @ 75 ohms	
Audio	Speaker R / L x 2W	
Certification	CE, FCC, UL	
Power Supply	DC 12V Power Adaptor, (AC100~240V, 50 / 60Hz Universal)	
Power management	VESA-DPMS; Consumption: 50W Max; Saving Mode: < 5W	
Net / Gross Weight	5.8	6.8