



15" TFT-LCD Monitor

IV-V151BN



SPECIFICATION	IV-V151BN
Screen Size	15"
Panel	Active Matrix, TFT LCD
Surface Treatment	Hard-coating (3H), Anti-Glare treatment
Active Area	304.128 (H) x 228.096 (V) mm
Display Type	XGA (1024x768)
Maximum Resolution	1024x768
Recommended Resolution	1024x768
Resolution Support	VGA, SVGA, XGA
Pixel Pitch	0.297mm
Display Colors	16.2 Million
Brightness	250 cd/m ²
Contrast Ratio	500:01:00
Response Time	12ms
Viewing Angle (H / V)	130° / 120°
Frequency	Horizontal: 30~61KHz ; Vertical: 50~75Hz
Frequency Sync.	H/V separated (TTL) Positive / Negative
Plug & Play	DDC 1 / 2B
VGA Input	15 Pin D-Sug
Video Input/Output	1 CH BNC IN / 1CH BNC OUT
Audio Input	1 CH RCA IN
Power	DC In
Power Supply	Power Supply AC Input: 100-240V~1.8A, 50-60HzDC DC Output: 12V/3.0A
Power Consumption	Power Consumption 25 Watt (Max.)
Front Control	Power, Menu, Down, Up, Auto Image Adjustment
OSD Function	Contrast, Brightness, Auto Image Adjust, H. Position, H. Phase, V. position, H. Width, Sharpness, Color Temperature, Hue, Saturation, Flesh tone, OSD position, Language, Recall, Volume
Built-in Speakers	2W x 2
Adjustable Stand	Tilt Adjustments
Safety & EMI	UL, CUL, FCC-B, CB, CE, TUV/GS
Wall Mountable	VESA 75
Dimensions (Pack)	16" (W) x 16.5" (H) x 5.38" (D) [407(W) x 420(H) x 136.5(D) mm]
Dimensions (Set Size)	13.63" (W) x 13.25" (H) x 5.5" (D) [346(W) x 337(H) x 140(D) mm]
Dimensions (Without Stand)	13.63" (W) x 11.63" (H) x 1.5" (D) [346(W) x 295(H) x 38(D) mm]
Weight	Net: 6 lbs (2.7 Kg) / Gross: 9 lbs (4.1 Kg)
Operation Conditions	Temperature: 0°C~50°C / Humidity: 10%~90% (%RH)
Storage Conditions	Temperature: -20°C~60°C / Humidity: 10%~90% (%RH)
Manufacturer Warranty	3 years parts, labor, 1 year LCD panel
Accessory	Power adapter, power cord, VGA cable, audio cable, User manual