



# 19" LCD Security Monitor

## IV-V191BN-B

### Features:

- . Fast response time of 5 ms
- . Wide viewing angle of 160°(H) /160°(V)
- . High contrast ratio of 800:1 (type)
- . Brightness of 300 cd/m<sup>2</sup> (type)
- . Resolution of 1280x1024 SXGA,
- . 3D comb filter to get a sharp and vivid picture.
- . Supports BNC connector for security application
- . Integrates two speakers of 2 watts
- . Looping with one BNC Video IN and one BNC Video OUT
- . Look compact and simple.
- . High display quality, reliability and space-saving



SPECIFICATION	IV-V191BN-B
<b>LCD Display</b>	Anti-glare type, 19" Active Matrix TFT LCD Panel
<b>Max. Resolution</b>	1280(H) x 1024(V) SXGA
<b>Pixel Pitch</b>	0.294 (mm)
<b>Color Depth</b>	16.7 million
<b>Contrast Ratio</b>	800 : 1 (Typ)
<b>Brightness</b>	300 cd/m <sup>2</sup>
<b>Viewing Angle</b>	Horizontal : 160° , Vertical : 160°
<b>Response Time</b>	5 ms (Typ, on/off)
<b>Image Processing</b>	3D Comb Filter
<b>Signal Input</b>	Analog D-sub; Composite BNC
<b>Audio-in (speaker)</b>	3 Watts x 2
<b>Connector</b>	D-sub, DC in, BNC IN x1, BNC OUT x1, Composite Audio-in
<b>Power Consumption</b>	50 Watts (Max.); 3 Watts (standby)
<b>Power Adapter</b>	AC Input: 100-240V~1.8A, 50-60HzDC DC Output: 12V/4.16A
<b>Front Control</b>	Menu, Down, Up, Auto adjustment, Power
<b>OSD Function</b>	contrast, brightness, auto adjustment, H. position, H. phase, V. position, H. width, sharpness, color temperature, OSD position, language, recall, volume
<b>Set Size</b>	16.7" (W) x 16.5" (H) x 6.9" (D) [425(W) x 419(H) x 174(D) mm]
<b>Set Size without stand</b>	16.7" (W) x 14.75" (H) x 2" (D) [425(W) x 375(H) x 50(D) mm]
<b>Weight</b>	Net: 11 lbs (5 Kg) / Gross: 14.8 lbs (6.7 Kg)
<b>Wall Mount</b>	VESA 75 (mm)
<b>Safety &amp; EMI</b>	UL, CUL, FCC-B, CB, CE, TUV/GS
<b>Warranty</b>	1 year on LCD panel and 3 years on parts and labor (after 10/15/2007).
<b>Accessory</b>	Power adapter, power cord, VGA cable, audio cable, user manual