



## 3.5" Wearable TFT Monitor

### IV-2535D

#### Features:

- . Compact 3.5" Size
- . Wearable Pouch for Hands-Free Operation
- . Dual power sources
- . CE / FCC approved
- . Do not need the second person to assist positioning and trouble shooting of the cameras



SPECIFICATION	IV-2535D
Screen Size	3.5 inches Digital TFT-LCD Panel
Resolution	320 RGB X 240 dots
Dot Pitch	Horizontal 70.8 degrees / Vertical 52.56 degrees
View Angle	Horizontal 60 degrees / Vertical 55 degrees (Typ.)
Color Structure	R.G.B. Strip
Backlight	2 Groups LED
Video Signal	NTSC/PAL auto-switch
Input Signal	1.0Vp-p combination video
Power	AA Alkaline Battery X 8 pcs or DC12V / Adaptor
Power Consumption	8W max.
Brightness	200 cd/m2 minimum (Typ.) / 250cd/m2 (Center of Diaplay)
Response Time	Typ. 15ms / Max. 30ms
Operation temperature	14 °F ~ 140 °F (- 10 °C ~ 60 °C)
Storage temperature	-4 °F ~ 158 °F (- 20 °C ~ 70 °C)
Outlook Size (L)x(W)x(D)	3.5" x 3.8" x 0.98" / 95 x 97 (W) x 25 mm
Weight	18.7 oz/ 530g (G.W.)
Accessories	Wristband / BNC with Cable / Power Cable / Backup Case