



CCTV Tester

IV-CCTV-TESTER

- . Connects to camera directly
- . Search/test for workable PTZ camera protocol
- . UTP cable connection test
- . Video signal strength test
- . RS485 connection test for PTZ camera



SPECIFICATION	IV-CCTV-TESTER
Signal Mode	NTSC/PAL automatically suitable
Display	2.5 inch LCD screen, 960 x 240 resolution
Video Input	1 channel BNC
Video Output	1 channel BNC
PTZ Controlling	
Communication	RS232, RS422 simplex and RS485
Protocol	Pelco D, P; Samsung, Panasonic or customized
Baud Rate	2400, 4800, 9600, 19200
Other Function	
Signal Generating	Output 1 channel video signal for testing monitor
UTP Cable Test	Test UTP cable connection state and display in the screen
RS485 Data Test	Test the RS485 data sent from controlling device
Operation	English OSD menu
Power	
Power Adapter	DC9V~12V
Battery	2 pcs 18490 standard batteries 3.6V, capacity 2800mAh included
Rechargeable	5 hours recharging time, work for 5 hours
Low Consumption	Sleeping mode, display battery power state
Other Parameters	
Work Temperature	-22°F ~ 158°F
Work Humidity	30%-90%
Dimension	6.7" x 3.9" x 1.9"