



Public View Monitors

IV-PVM24DIS

Features:

- . PIXIM Wide Dynamic 690 HTVL-E Camera Built-in
- . LED backlight, 40% power saving
- . 3D Noise reduction & Comb filter
- . Camera Loop out (BNC)
- . SD-Card reader, HDMI, Composite video support
- . Auto Switch between different channel on/off
- . On screen Warning Message on/off
- . Super Slim Metal housing design
- . Full glass cover front face
- . Movement Sense wake up
- . 2-Axis adjustment, Easy Access to Camera
- . Full function remote control
- . Safety working voltage
- . Cooling fans build in



Specification		IV-PVM24DIS	
Display	Screen Size	23.6 inch	
	Aspect Ratio	16:9	
	Backlight	LED	
	Viewing Angle	170°/170°	
	Resolution	1920 x 1080	
	Response Time	5ms	
	Contrast Ratio	1000:1	
	Brightness	300 cd/m ²	
Input	VGA	1	
	CVBS (BNC)	1	
	HDMI	1	
	S-Video	1	
	Audio (R/L)	1	
Output	Camera (BNC)	1	
	CVBS (BNC)	1	
Power	Consumption	< 45W	
	Voltage	AC 100-240V 50-60Hz	
System	PAL / NTSC Auto Detection & OSD Control		
WDR Camera			
Sensor	Sensor	1/3 " DPS Sensor	
	Video Format	PAL / NTSC	
	Resolution	690 HTVL-E	
	Mini illumination	0.1Lux	
	S/N Ratio	≥ 50 db (AGC OFF)	
Control	WDR Control	Medium, Normal, Low, High	
	BLC	ON,OFF	
	AGC	Normal, Low, High	
	White Balance	Tracking White Balance, Auto White Balance(ATW)	
		(Auto White Balance) 2200-10000 K	
	D/N	OFF, External Control, Auto; ON	
	SYNC Mode	Internal	
Power	Voltage	DC 12V	
	Current	<150 mA	
Lens	2.8 - 12 mm		
PVM Size	21" x 16"		
PVM Weight	Approx. 16 lbs.		
Temperature	14 °F ~ 122 °F / -10°C ~ 50 °C		