



2MP 4 in 1 Indoor / Outdoor IR Bullet with 247 Color Light

IV-BUF282MP-FH-247color

Features:



- . 2MP HD TVI output(AHD/TVI/CVI)
- . 2.0MP@TVI/AHD & 2.0MP @ CVI & CVBS video output . Fixed lens 2.8mm
- . IR distance: 64ft
- . Support low illumination,warm light day night full color
- . Support ICR switch, 2D-DNR, Day/night, D-WDR
- . DC 12V IP66



Use the toggle switch to select the four video output modes:

Select your video protocol by switching the positions of the toggle switches per the below diagram.

The toggle switches are located at the end of the camera cable



Specification	IV-BUF282MP-FH-247color
Horizontal Resolution	2MP@ TVI/AHD & 2MP@ CVI & CVBS
Image Sensor	1/2.5" CMOS
Effective Pixels	1920 x 1080
Signal System	PAL / NTSC
S/N Ratio	≥50dB (AGC Off)
Min. Illumination	0.1Lux @F1.2 (AGC on) 0 Lux IR LED on
Video Output	TVI /AHD (2MP@25fps, 2MP /1080P@30fps); CVI (2MP@25fps, 1080P@30fps); Analog (1280x576, 1280x480)
Lens	Fixed lens 2.8mm
Day&Night	Support (ICR)
White Balance	Auto
OSD	English / Chinese
UTC	Support
White Balance	Auto/Auto-ext/Preset/Manual
Privacy Mask	Off / 0~15 Zones
IR Distance	64 ft
Connector Video	BNC
LED	2 PCS 3500K soft warm light
Video Output	TVI / CVI / AHD / CVBS
Power Supply	DC12V±10%
Power Consumption	3W (Max. 3.6W with IR cut filter on)
Weight	1.28lbs (580g)
IP Rating	IP67
Working Temperature/Humidity	-4°F ~ 122°F (-20°C ~ 50°C)
Working Humidity	Humidity 90% or less (non-condensing)
Dimension	Ø 4.75" X 3.75" (h)
Weight	1.65 lbs.
Dimensions	Ø5.2" x 3.94" (Ø132mm x 100mm)