



IP Wall Speaker

IV-SP-S11

Features:

- Transfer loud and excellent sound.
- IP 55 waterproof design for installation on exterior of building.
- 48K OPUS Audio Codec enables excellent sound quality .
- Compatible with IP, SIP devices (IPPBX, IP Phone) via SIP.
- Compatible with IP Camera VMS via ONVIF.
- Support Pre-recorded messages.
- Support HPPT API for alarm in transmit.



Specification	
Audio	
Decoding	OPUS 48 kHz, MP3 44.1 kHz, G.722 ADPCM 16 kHz, G.711 PCMU 8 kHz, G.711 PCMA 8 kHz
Speaker	
Max SPL	101dB
Frequency response	80Hz~20KHz
Frequency Range	500-2KHZ +-10dB 400-12KHZ +-20dB
Harmonic Distortion	0.1@1kHz
Signal to Noise Ratio	91dB
Network	
Security	Password protection, IP address filtering, Digest authentication, User access log, firewall
Network Protocol	SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP
Network Interface	10/100 Base-TX, RJ45
VoIP	Support for SIP protocol for intergration with VoIP systimes, intergrated with SIP/PBX. Support SIP features: secondary/backend SIP server, IPv4 (IPv6 futhur) Support codecs: OPUS, G711U, G711A, GSM, MP3
Amplifier	
Amplifier Description	Built-in 15W Amplifier
General	
Operating Temperature	-30℃ — +60℃
Operating humility	5%-85%
Material	ABS (IP55 water-proof)
Rate Power	15W
Power Supply	PoE or DC 12V/24V
Installation	Wall Mounted
Dimensions	296 x 196 x 157 mm
Net Weight	2.4 KG
Languages	English
Warranty	2 years
Package Includes	Network Wall Speaker User Manual