

# 4 x 5MP LightHunter Multi-sensor VF Network Dome Camera

IV-MV271354X5MP-CA



## Features

- One IP with four channels
- Support multiple intelligent functions, different function of each channel can be enabled at the same time to satisfy various analysis requirement
- Pan, tilt, rotation angle of each lens can be adjusted independently, suitable for more complicated scenes
- 4 channel video output, 2880\*1620@30fps in the main stream of each channel, provide high definition image
- Ultra 265, H.265, H.264, MJPEG

- Smart intrusion prevention, support false alarm filtering, realize accurate detection based on specific target
- Face capture, automatic selection of best snapshots and face attribute collection
- People Counting, support people flow counting and crowd density monitoring, suitable for different statistical scenarios
- LightHunter technology ensures ultra-high image quality in low illumination environment
- Up to 130 dB Optical WDR (Wide Dynamic Range)
- IP67 ingress

## Specifications

Camera	Description
Channel	4
Sensor	1/2.7" CMOS
Min. Illumination	Colour: 0.002 lux (F1.6, AGC ON) 0 lux with IR on
Day/Night	IR-cut filter with auto switch (ICR)
Shutter	Auto/Manual, 1 ~ 1/100000s
Adjustment Angle	Pan: 0° ~ 360°, Tilt: 0° ~ 65°, Rotate: 0° ~ 355°
S/N	>56dB
Lens	Description
Focal Length	2.7-13.5mm
Iris	F1.2
Iris Type	DC-Iris
Field of View (H)	(W)110.3°~(T)31°
Field of View (V)	(W)57.1°~(T)17.5°
Field of View (D)	(W)130.2°~(T)67.4°
Lens Type	5X
DORI	Description
DORI Distance(Detect)	70.9m~247.5m(232.5ft~812.0ft)
DORI Distance(Observe)	28.4m~99.0m(93.0ft~324.8ft)
DORI Distance(Recognize)	14.2m~49.5m(46.5ft~162.4ft)
DORI Distance(Identify)	7.1m~24.8m(23.3ft~81.2ft)
Illuminator	Description

Illumination Distance(IR)	50 m (164.0 ft)
Wavelength	850 nm
IR On/Off Control	Auto/Manual
<b>Image</b>	Description
Digital Noise Reduction	2D/3D DNR
Smart IR	Support
White Balance	Auto; Outdoor; Fine Tune; Sodium Lamp; Locked; Auto2
Flip	Normal; Flip Vertical; Flip Horizontal; 180°; 90°Clockwise; 90°Anti-clockwise
HLC	Support
Defog	Digital Defog
<b>Intelligent</b>	Description
Smart Intrusion Prevention	Cross line detection, Intrusion detection, Enter area detection, Leave area detection
<b>Events</b>	Description
UMD (Ultra Motion Detection)	Support
Tampering Detection	Support
Audio Detection	Support
<b>Network</b>	Description
Protocols	IPv4; IPv6; IGMP; ICMP; ARP; TCP; UDP; DHCP; PPPoE; RTP; RTSP; RTCP; RTMP; DNS; DDNS; NTP; FTP; UPnP; HTTP; HTTPS; SMTP; 802.1x; SNMP; QoS; SSL/TLS; SSH
Compatible Integration	ONVIF (Profile S, Profile G, Profile T, Profile M); API; SDK
User/Host	Up to 32 users. 3 user levels: administrator, common user and operator
Security	Password protection; Strong password; HTTPS encryption; Export operation logs; Basic and Digest Authentication for RTSP; Digest Authentication for HTTP; TLS 1.2; WSSE and Digest Authentication for ONVIF
Client	GuardStation
Web Browser	Plug-in required live view: IE 10 and above, Chrome 45 and above, Firefox 52 and above, Edge 79 and above; Plug-in free live view: Chrome 57.0 and above, Firefox 58.0 and above, Edge 16 and above
<b>Storage</b>	Description
Edge Storage	Micro SD, up to 1 TB
Network Storage	ANR; NAS (NFS)
<b>Video</b>	Description

Video Compression	Ultra 265; H.265; H.264; MJPEG
H.264 Code Profile	Baseline profile, Main profile, High profile
Video Bit Rate	128 Kbps ~ 16 Mbps
U-code	Support
ROI	Up to 8
Video Stream	Triple streams
OSD	Up to 10 OSDs
Privacy Mask	Up to 8
<b>Audio</b>	<b>Description</b>
Audio Compression	G.711U; G.711A
Two-way Audio	Support
Sampling Rate	8 KHz
<b>Interface</b>	<b>Description</b>
Audio I/O	1/1
Alarm I/O	3/2
Built-in Mic	Support
Network	10M/100M/1000M Base-TX Ethernet
<b>Certification</b>	<b>Description</b>
EMC	CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 50130) FCC (FCC 47 CFR part15 B)
Safety	CE-LVD (EN 62368-1) UL/CUL (UL 62368-1, CAN/CSA C22.2 No. 62368-1)
Environment	CE-RoHS (2011/65/EU;(EU)2015/863); WEEE (2012/19/EU)
Protection	IP67 (IEC 60529)
<b>General</b>	<b>Description</b>
Power	DC 24V ± 25%, AC 24V ± 25%, PoE (IEEE802.3bt)
Built-in DC12V Output	Support
Power Interface	Wires with cold-pressed terminal
Dimensions	φ 318mm * 136.6mm
Weight	4.77Kg (10.52lb)
Working Environment	-30 °C ~ 60 °C (-22 °F ~ 140 °F), Humidity: 5%~95% RH
Storage Environment	-40 °C ~ 70 °C (-40 °F ~ 158 °F), Humidity: 5%~95% RH

Surge Protection

6KV

## Dimensions

